

Mixer / Pump

MX-10

The most popular refractory mixer/pump combination in service across the globe!

Can be used for:

Refractory Pumpcast Applications
Refractory Shotcrete Applications
3/8" (1 cm.) Aggregate Shotcrete



Blastcrete Refractory Pumps are the
most economical,
versatile, simple, and safe
refractory pumps ever built!



Anniston, AL
800-235-4867
www.blastcrete.com



Standard Swing Out Receiving Hopper



Reliable Shotcrete Delivery



The MX-10 has been the industry standard since 1996.

Features

- 2200 PSI Piston Face Pressure
- 2200 lb. Capacity High Torque Pan Mixer
- Simple Swing Out Receiving Hopper for Easy Access to Swing Tube Section for Cleaning and Maintenance
- Fill Rite Water Meter
- Forklift Tubing Mounted to Lower Hopper for Easy Flat Pack Removal
- 20 ga. Dousing Bucket for Fast Water Introduction
- CE Certification
- 99 HP Turbo Charged John Deere Diesel Engine

Options

- 2000 PSI Hydraulic Pressure Washer
- Automatic Lubrication System
- Spare Tire Mounted
- Skid Mount
- Blastcrete Computerized Water Metering System

Specifications

Pump	3" x 24" Swing Tube (7.5 cm. x 60 cm.)
Pumping Pressure	2200 psi (152 bar)
Mixer	2200 lb. Capacity (1000 kg.)
Output	12 yd ³ /hr. (9 m ³)
Discharge Outlet	3" (7.5 cm.)
Hopper	2500 lb. Capacity (1130 kg.)
Operating Platform	22 ft ² (2 m ²)
Crane Pickup	4 point center pickup
Electrical	Solid State
Trailer	Dual 7000 lb. Axles (3175 kg.)
Dimensions	204" x 88" x 117" (510 cm. x 220 cm. x 292.5 cm.)
Weight	9000 lbs. (4500 kg.)

Power Options

Dual Electric Motors

Note: Output, conveying distance and height will vary depending on the mix, job conditions, mixing speed, pumping speed and diameter of conveying system.

Blastcrete Equipment Company 2000 Cobb Avenue P.O. Box 1964 Anniston, AL 36202
800-235-4867 (Toll Free) 256-235-2700 256-236-9824 (Fax) www.blastcrete.com